

KROMA TELECOM

## TP7016 – 16-key USER PANEL



This user panel is capable of the following commands:

- Talk Only: Audio is sent from the panel to its assigned destination (one way only).
- Listen Only: Audio is received from the source (one way only).
- Talk & Listen: Audio is sent and received. It's a two-way communication.
- Remote One Way: The crosspoint is activated at a panel but is produced between third parties (example: one user panel may activate the communication between a beltpack and the CCUs). One way only.
- Remote Both Ways: Same as above, in both ways.
- Remote Volume: For remote crosspoint level adjustment.
- Volume +: For increasing local crosspoint level (up to +12dB on a +1dB basis on the incoming audio).
- Volume -: For decreasing local crosspoint level (up to -12dB on a -1dB basis on the incoming audio).

### TECH SPECS:

Dimensions	1 unit high/19", 150 mm deep
Weight	2,5 Kg
Power supply	+15v, 500mA external PS
Number of XPT keys	16
Mic preamplifier	+50dB to +75 dB (input -63dB)
Speaker preamplifier	10w at 4Ω
Signal format	44,1Khz sampling, 16 audio bits + 8 data bits
Connections	RJ45 (digital) SUBD9M (analogue)
Aux analogue I/O	nominal level 4 dBv Max level 12dBv Bandwidth 150Hz-10kHz SNR > 80 dB THD < 0.2% a 4 dB


---

KROMA TELECOM

La Granja 80 – Pol Ind Alcobendas  
28108 MADRID – SPAIN

Tel +34.91.661.4514 Fax +34.91.661.5875 Email sales@kromatelecom.com

[www.kromatelecom.com](http://www.kromatelecom.com)



KROMA TELECOM

At the front panel we might find:

- An XLR input for the microphone (dynamic or electret, switchable by jumper hardware).
- A jack connector for the headset.
- A mute key (with led).
- Two potentiometers: for the main audio and the audio from the aux I/O.
- Two leds for power and matrix communication.
- 16 programmable double-led crosspoint keys (PTT, Latching or both). Labels are created by Indico config programme.

At the rear panel we might find:

- Digital port: RJ45 connector for connecting the panel with the matrix thru a twisted 8-wire FTP CAT 5 cable.
- Jack connector for external PS (+15v).
- An aux analogue input/output for them for connecting it to Kroma Analogue Intercom, for receiving 4-wire external audio sources (on-air local monitoring) or for sending the audio to external equipments.
- A GPIO for tally purposes such as on air, video switchers, etc. Input is activated by tension (+12v), output is activated by contact closure.



---

KROMA TELECOM

La Granja 80 – Pol Ind Alcobendas  
28108 MADRID – SPAIN

Tel +34.91.661.4514 Fax +34.91.661.5875 Email [sales@kromatelecom.com](mailto:sales@kromatelecom.com)

[www.kromatelecom.com](http://www.kromatelecom.com)